


PSL Range

Pressure Limiting Valves

Scope of Use / Specification Sheet

RMC's PSL Pressure Limiting Valves regulate the inlet supply line pressure to a preset maximum preventing over-pressure situations. PSL Pressure Limiting Valves are ideal for installation with high pressure storage water heaters, water meter assemblies, water softeners etc.



Product List

Model		350kPa	500kPa	600kPa
PSL50X	Female Parallel	PLX1504	PLX1505	PLX1506
	Male Compression	PLX1501	PLX1502	PLX1503
PSL75X	Male Tapered	PLX2010	PLX2011	PLX2012
	Male Compression	PLX2001	PLX2002	PLX2003

Description

PSL Pressure Limiting Valves are of an inline barrel design. The valve remains open if the pressure in the supply line falls below the maximum preset pressure.

Valves are available in 15mm and 20mm configurations.

Materials

Body	Lead Free DZR Brass
Internal Parts	Polysulfone, polyphenylsulfone and stainless steel
O-Rings / seal	Viton® / NBR
Spring	Stainless Steel
Piston	Polysulfone

Features and Benefits

- High pressure and temperature tolerances
- Suitable for a wide variety of pressure limiting applications
- Stainless steel seat
- Extended service life
- Dezincification resistant
- Meets Australian Standard for potable water supply
- Suitable for horizontal or vertical installation. Valve designed to work effectively in either orientation
- Available in fixed outlet pressure settings of 350kPa, 500kPa and 600kPa

Note

This valve is of a piston based design and needs a vent hole to ensure operation. If this valve is exposed to high inlet pressures (e.g. Poor water conditions or under water hammer conditions), damage to the valve can result in water leaking through the vent hole.

This hole should not be covered or filled in any way to prevent malfunction of this valve. It is recommended to not install this valve in enclosed spaces or areas where the venting of water has a potential to cause damage. The use of liquid thread sealant is not recommended.


PSL Range Pressure Limiting Valves

Specifications

Model	DN Size	Inlet/Outlet Fittings	Standard Pressure Settings Available (kPa)	Maximum Inlet Pressure (kPa)	Maximum Temperature
PSL50X	15mm	Female Parallel	350, 500, 600	2000	80°C
	15mm	Compression	350, 500, 600	2000	80°C
PSL75X	20mm	Male Tapered	350, 500, 600	2000	80°C
	20mm	Compression	350, 500, 600	2000	80°C


Flow rates

Nominal diameter	Flow rate (maximum)
15mm	50L/min at 700kPa inlet
20mm	60L/min at 700kPa inlet



Dimensions

Model	In/Out Fittings	Width (W)	Diameter (D)	Connection (C)
PSL50X	Female Tapered	92	34.5	Rp 1/2
	Compression	115	34.5	15Cn
PSL75X	Male Tapered	92	34.5	Rp 3/4
	Compression	92	34.5	20Cn



Note: All measurements in mm unless otherwise stated.

Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three – Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500. This product is compliant to the Lead Free requirements of the National Construction Code Volume Three. For further Scope of Use, please visit www.rmc.com.au/resources.

Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit www.rmc.com.au/warranty to view the warranty statement in full and for further important information.

Standards and Approvals



rmc.com.au | 1800 810 803 | sales.au@rmc.com

Reliance Worldwide Corporation (Aust.) Pty. Ltd. reserves the right to change any product specification or information contained in this publication at any time and without notice. All diagrams are illustrative only. Please consult OEM instructions and AS/NZS 3500 for all installations. ABN 71 004 784 301 | SS24015_2024_v2