


Water Ball Valves

Scope of Use / Specification Sheet

RMC Water Ball Valves are a proven industry leading design and available in a range of sizes, in both right angle and straight configurations. RMC can also supply a range of fittings (compression, capillary and more) to suit most connection needs.



BVX2506

Product List

Model	Size	Order Code
Water Service Ball Valve - Long Handle and Lockable	15mm	BVX1506
	20mm	BVX2006
	25mm	BVX2506
	32mm	BVX3206
	40mm	BVX4006
	50mm	BVX5006

Features and Benefits

- Forged Lead Free DZR Brass Body
- Bottom loading, dual O-Ring sealed stem
- Resilient seats
- Lockable in either open or closed position
- Long life performance through its high quality components
- Quality guaranteed Water Marked product

Installation Conditions

Working Temperature Range	0°C to 60°C
Maximum Working Pressure	2500kPa
Medium	Water
Handle Colour	Blue

Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three – Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500. This product is compliant to the Lead Free requirements of the National Construction Code Volume Three. For further Scope of Use, please visit www.rmc.com.au/resources.

Standards and Approvals



Lead Free

AS 5830.1
WM-022614

Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit www.rmc.com.au/warranty to view the warranty statement in full and for further important information.

Water Ball Valves

Materials		
1	Body	Lead Free DZR Brass
2	Bonnet	Lead Free DZR Brass
3	Seat	PTFE
4	Ball	Lead Free DZR Brass
5	Stem	Lead Free DZR Brass
6	O Ring	NBR
7	O Ring	HNBR
8	Lever	SS304
9	Lever Nut	SS304

Dimensions							
Model	Size (Rp)	L	L1	L2	L3	ØD	H
BVX1506	1/2"	66	16	100	17	14.8	50
BVX2006	3/4"	73.4	17	100	17	19	53
BVX2506	1"	84.6	20	125	19	24	64.3
BVX3206	1 1/4"	102.5	21.4	135	22	32	71.5
BVX4006	1 1/2"	112.3	22.5	140	23	40	78.5
BVX5006	2"	132.6	27	140	27	50	86.5

Note: All measurements in mm unless otherwise stated.

