

WHY RWC WATER METERS?

Reliance Worldwide Corporation (RWC) supplies a range of water meters suitable for hot and cold water, domestic, commercial and industrial applications.

Our meters conform to Australian standards and are available in configurations suitable for each state in Australia.

We also supply water valves that conform to selected international standards. A range of automatic reading products and logging/monitoring products are available to compliment our water meter products.



RWC

YOUR GUIDE TO WATER METERS




Contents of this brochure are subject to change, please visit our website for most up-to-date product information.



Domestic



Commercial



Industrial

RWC

☎ 1800 810 803

✉ sales.au@rwc.com

🌐 rmc.com.au

27-28 Chapman Place,
Eagle Farm QLD 4009, Australia

RWC Reliance Worldwide Corporation (Aust.) Pty. Ltd.
ABN 71 004 784 301 | MNL0001_2024-v5

rmc.com.au

RWC WATER METERING PRODUCT RANGE

- Positive Displacement Meters
- Multijet Water Meters
- Octave Ultrasonic Meters
- Woltman Meters
- Hot Water Meters
- Sub Metering Kits
- Tapping Kits
- Ball Valves
- Tapping Bands
- Ferrule Cocks & Bends
- Meter Boxes
- Standpipes
- Reed Switches & Pulse Outputs

Positive Displacement Meter

Size	15-20mm
Pulse	1P / 5l
Max. Water Temp.	50°C
Max. Working Pressure	1600kPa
Approval	NMI Approved WaterMark Approved



Sub Metering Kits

- 20mm
- Available in different configurations; Meter Thread - STD copper connection NSW Thread - STD copper connection
- Also available in SharkBite® copper and PEX connections




Multijet Meter

Size	20-25mm, 50mm
Pulse	1P / 10l
Max. Water Temp.	50°C
Max. Working Pressure	1400kPa
Approval	NMI Approved WaterMark Approved (20mm, 25mm only)



Tapping Kits

- Rapid tap for 20-25mm tapping
- For pressure and dry taps
- Major tap for 32-50mm
- Watgas for 150mm tapping



Octave Ultrasonic Meter

Size	50-200mm
Pulse	1P / 10l / 100l / 1000l
Max. Water Temp.	50°C
Max. Working Pressure	1600kPa
Approval	NMI Approved



Ball Valves

- Watermarked
- Long, straight or short handle
- Lockable, right angle configuration
- Stainless Steel option available



Woltman Meter

Size	50-200mm
Pulse	1P / 10l / 100l / 1000l
Max. Water Temp.	60°C
Max. Working Pressure	1600kPa
Approval	NMI Approved



Tapping Bands

- WaterMark Approved (select types and sizes)
- AC/DI & PVC Pipe
- 3/4 - 2" BSP outlet



